

## Model and Description

LAD	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Model	Dimension (Dia): 40: 40mm 52: 52mm 55: 55mm 100: 100mm	Lighting type: L:Steady C:Flashing	Sound type: L:Intermittent C:Continuous	Colour: R-Red Y-Yellow G-Green B-Blue W-White	Installation: Z1-Support tube direct mounting Z2-Support tube with a bracket Z3-Support tube with a black fixing plate Z4-Fixing base Z5-three screws direct mounting Z6-Fixing base	Operating voltage: 22-AC.DC 12V 23-AC.DC 24V 26-AC.DC 110V 31-AC 220V

## Specification

Flash frequency	140-60 times/min.
Material	Lamp shade: PC Base: ABS Support tube: AL
Ambient Temperature	-20℃~70℃
Ambient Humidity	≤90%RH
Wind pressure resistant strength	150Km/h
Power frequency withstand voltage	AC2500V
Rated insulation voltage	AC690V
Max.voltage fluctuation	±10%Ue
Altitude	≤2000m
Rated frequency	40Hz~60Hz
Degree of protection	IP54
Buzzer	Sound level:85dB Min.

## Picture

LAD-100L <input type="checkbox"/> /R Rotating beacon 	LAD-52L <input type="checkbox"/> /RGY 	LAD-55L <input type="checkbox"/> /RG-Z5 Tower lights 	LAD-55L <input type="checkbox"/> /BGYR-Z3 Tower lights 
LAD-55L <input type="checkbox"/> /R-Z2 Tower lights 	LAD-55L <input type="checkbox"/> /WBGYR-Z4 Tower lights 	LAD-55L <input type="checkbox"/> /GYR-Z6 Tower lights 	Z1 Support tube 
Z2 Support tube with a bracket 	Z3 Support tube with a Black fixing plate 	Z4 Fixing base 	Z5 Three screws direct mounting 
Z6 Fixing base 			